



VACUUM SEALER SU-604CC

Floorstanding unit. 40m³/h. 465+465 mm.



FEATURES AND BENEFITS

- ✓ Powered by Busch.
- ✓ Vacuum controlled by sensor.
- ✓ Vacuum PLUS.
- ✓ LCD colour screen: all information at a glance.
- ✓ Backlit touch keyboard.
- ✓ Programmable: 25-programme memory. Blocking option.
- ✓ "Pause" button.
- ✓ Phased vacuum programme.
- ✓ Detection of the evaporation of liquids.
- ✓ Double seal.
- ✓ Cordless sealing bar.
- ✓ Progressive decompression.
- ✓ Vac-Norm ready with Automatic decompression.
- ✓ Stainless steel body and chamber.
- ✓ Damped transparent lid of high durability polycarbonate.
- ✓ Dry-oil programme for drying the pump.
- ✓ Working hours counter for oil changes.
- ✓ Safety system with protection against vacuum failure.
- ✓ NSF-listed.

INCLUDES

- ✓ BUSCH pump.
- ✓ Sensor Controls.
- ✓ 25 programmable settings.
- ✓ Vacuum PLUS: up to 10 seconds of extra vacuum pull.
- ✓ Soft air function.
- ✓ Clear methacrylate lid.
- ✓ "PAUSE" function.
- ✓ Liquid detection system.
- ✓ Dry oil cycle.
- ✓ NSF Approved.
- ✓ Filling plate.

OPTIONAL

- ☐ Inert gas
- ☐ Printer
- ☐ Vacuum packing bags
- ☐ External vacuum kit for Vac-Norm, containers and accessories
- ☐ Bag cutting kit
- ☐ Support for liquid packaging
- ☐ Additional filling plates

SALES DESCRIPTION

Two sealing bars (465+465 mm.)
40 m³/h Busch vacuum pump.
Vacuum controlled by sensor.



sammic | www.sammic.com
Food Service Equipment Manufacturer

Polígono Basarte, 1.
20720 Azkoitia, Spain

phone +34 943 15 72 36
sales@sammic.com



Project	Date
Item	Qty
Approved	

specification sheet
update 11/21/17

FOOD PRESERVATION AND SOUS-VIDE
VACUUM PACKING MACHINES - "SENSOR ULTRA" LINE



VACUUM SEALER SU-604CC

Floorstanding unit. 40m³/h. 465+465 mm.



TECHNICAL SPECIFICATIONS

Pump capacity: 40 m³/h

Bar length: 465 mm + 465 mm

Total loading: 1100 W

Vacuum pressure (maximum): 0.5 mbar

Internal dimensions

✓ Width: 672 mm

✓ Depth: 481 mm

✓ Height: 200 mm

External dimensions (WxDxH)

✓ Width: 740 mm

✓ Depth: 566 mm

✓ Height: 997 mm

Net weight: 145 Kg




Noise level (1m.): -- dB(A)

Background noise: 32 dB(A)

Crated dimensions

660 x 840 x 1200 mm

Gross weight: 116 Kg.



AVAILABLE VERSIONS

1140817 Vacuum packing machine SU-604 CC 230-400/50/3N

* ask for special versions availability

ACCESORIES

- ☐ Bag cutting kits
- ☐ Filling plates
- ☐ Liquid insert plates
- ☐ Vac-norm external vacuum kits
- ☐ Vac-norm containers
- ☐ Smooth bags for vacuum packing
- ☐ CG2 Desktop printer for SU vacuum packing machines *
- ☐ Thermal labels for CG2 printer

sammic | www.sammic.com
Food Service Equipment Manufacturer

Polígono Basarte, 1.
20720 Azkoitia, Spain

phone +34 943 15 72 36
sales@sammic.com



Project

Date

Item

Qty

Approved

specification sheet
update 11/21/17

FOOD PRESERVATION AND SOUS-VIDE
VACUUM PACKING MACHINES - "SENSOR ULTRA" LINE