



## PI-30

### STAINLESS STEEL CONSTRUCTION

- Construction in stainless steel.
- Lateral stirrers covered with silicon carbide abrasive (approved by NSF).
- ° Aluminium base plate lined with silicon carbide abrasive (approved by NSF), easily removable for cleaning purpose.
- Auto-drag of waste to the drain.
- Energy optimisation thanks to engine optimization.
- Lifiable transparent polycarbonate cover, complete with locking and safety device.
- Aluminium door with hermetic seal and safety device.
- Waterproof control board (IP65): Improved reliability against moisture and water splash.
- Water inlet system with non-return air break.
- PI-30: water inlet system fitted with electric valve.
- Auxiliary contact for external electric valve.
- Timer 0-6min and continuous operation.

#### DEFAULT EQUIPMENT

#### OPTIONAL EQUIPMENT

- St. st. complete with filter with no-foam feature.

### TECHNICAL SPECIFICATIONS

Hourly production: 600 Kg / 720 Kg  
 Load capacity per programme: 30 Kg  
 Timer (min-max): 0' - 6'  
 Loading: 730 W

#### External dimensions

- Width: 622 mm
- Depth: 760 mm
- Height: 950 mm

#### external dimensions with support

- height with support: 546 mm
- depth with support: 760 mm
- height with support: 1255 mm

Net weight: 60 Kg



ER-0437/L96 **UNE-EN ISO 9001**  
 SAMMIC, S.L. (Sociedad Unipersonal)  
 Basarte, 1 - 20720 AZKOITIA - www.sammic.com