



DISHWASHER UX-150SBC 400/50/3N DD

Rack size 600 mm x 500 mm and door clearance 430 mm. Double-skinned hood.

P/N 1303460



washing performance.

Designed to last

- ✓ “Flow” opening mechanism: allows the hood to be raised with less effort
- ✓ High load capacity 43 cm: suitable for GN 1/1 and Euronorm
- ✓ Stainless steel surface filters for greater stability and resistance during intensive use

Premium warewashing

- ✓ Soft start: progressive start-up of the washing pump to protect fragile items.
- ✓ Top panel: it allows quick and intuitive reading of information, ideal for corner installations.
- ✓ Colour LCD Display: intuitive communication of the machine status by means of messages, colour codes and icons.
- ✓ Dedicated cycles: selection of the ideal washing programme using icons.
- ✓ Adaptable: allows the main parameters of the machine to be adjusted to the needs of each user.
- ✓ TEMPERATURE DISPLAY
- ✓ Wash Plus+ function: increases the intensity of the wash cycle for greater cleaning performance
- ✓ Control panel with IP65 humidity protection.

You will never WASH ALONE

- ✓ Tech-Services: our team of technicians will help you so that your machine is always ready for use.
- ✓ Design Services: tell us what your needs are and we will advise you.
- ✓ 60 years of experience and know-how at your disposal.

INCLUDES

✓ Rinse aid pump.	✓ Detergent Dispenser
✓ Drainage pump with level sensor. Proactive tank water renewal.	✓ 1 basket for glasses and pots.
	✓ 1 basket for plates.
	✓ 1 cutlery insert.

ACCESSORIES

<input type="checkbox"/> Tables for pass-through dishwashers	rack conveyors
<input type="checkbox"/> Central sorting tables	<input type="checkbox"/> Dosing equipments for AX / UX hood-type dishwashers
<input type="checkbox"/> Double connection central sorting table	<input type="checkbox"/> Tables for connecting two hood-type dishwashers
<input type="checkbox"/> Prewashing tables for pass-through and rack conveyor dishwashers	<input type="checkbox"/> External control panel for UX pass-through dishwashers
<input type="checkbox"/> Connecting tables for pass-through dishwashers and	<input type="checkbox"/> Special baskets for plastic glasses
	<input type="checkbox"/> 600 x 500 mm baskets

SPECIFICATIONS

Basket dimensions: 600 mm x 500 mm

Useful height: 430 mm

Cycles: 6

Cycle duration: 60 / 90 / 100 / 150 / 210"

Production baskets / hour: 60 / 40 / 36 / 24 / 17

Boiler capacity: 12 l

Wash tank capacity: 25 l

Consumption and savings

- ✓ Water consumption/cycle: 3 l
- ✓ Automatic switch-off: 120'

Energy consumption

WARE WASHING
PASS-THROUGH DISHWASHERS

product sheet
updated 28/01/2025

SALES DESCRIPTION

Top panel.

Sani-Control: guaranteed disinfection.

Double-walled hood: insulation and energy efficiency.

High-performance stainless steel wash arms.

3-stage filtering system.

Sani-Control guarantee

- ✓ GUARANTEED DISINFECTION in compliance with standard DIN 10534.
- ✓ THERMAL LOCK function: Ensures that rinsing will be carried out at the ideal temperature to disinfect the dishes.
- ✓ CONSTANT HIGH TEMPERATURE RINSE system for optimal disinfection.
- ✓ The PRESSURE PUMP guarantees effective high-pressure rinsing
- ✓ WRAS certified.

New recessed bodywork

- ✓ Ergonomic design with rounded corners to prevent the accumulation of dirt and facilitate cleaning.
- ✓ Compact tank volume (50% water saving compared to the previous range).

Double-Walled (Ultra ISO)

- ✓ Double-Walled Structure: thermo-acoustic insulation to attenuate the sound level and improve energy efficiency

High performance washing arms

- ✓ Stainless steel nozzles that ensure the distribution of washing water with proper angles and precise jets.
- ✓ Optimal washing results.
- ✓ Easy removal of the diffusers without tools for maintenance and cleaning.

3-stage filter system: surface, tank and extraction

- ✓ Keeps the washing water in optimal conditions to maintain constant





DISHWASHER UX-150SBC 400/50/3N DD

Rack size 600 mm x 500 mm and door clearance 430 mm. Double-skinned hood.



P/N 1303460

Loading

- ✓ Pump: 1500 W / 2 Hp
- ✓ Tank: 3000 W
- ✓ Boiler: 9000 W
- ✓ Total loading: 10500 W
- Electrical supply: 400 V / 50 Hz / 3N~ (16 A)
- External dimensions (W x D x H)
- ✓ Width: 730 mm (Wide with handle: 810 mm)

✓ Depth: 760 mm (Bottom with handle: 835 mm)

✓ Height: 2080 mm / 1572 mm

Net weight: 130 kg


Wash temperature: 65°C

Rinse temperature: 87°C

Crated dimensions

840 x 860 x 1600 mm

WARE WASHING
PASS-THROUGH DISHWASHERS



sammic | www.sammic.com
Food Service Equipment Manufacturer

Polígono Basarte, 1.
20720 Azkoitia, Spain
phone +34 943 15 72 36
sales@sammic.com



Project	Date
Item	Qty
Approved	